

9600 SERIES: COMPOSITE VIDEO DECODER MODULE

TECHNICAL SPECIFICATIONS

FEATURES

- Real-time, high-quality decoding of full motion video for video-over-IP applications
- Standards-based, H.264 algorithms (HP/MP/BP)
- Supports NTSC/PAL Formats
- Transmit video at rates as low as 64Kbps, up to 10Mbps
- RTP/UDP and TS/UDP Protocols
- Video/Audio/Data multiplexing IAW MPEG-2 Transport Standard
- MISB-Compliant
- Fully configurable network interface
- Latency <100ms
- Stereo/dual-channel audio outputs
- MPEG-1 Layer II Audio Compression
- IRIG-B Overlay
- Remote Set-up via Switch/Control Module
- Multi-channel Packaging with 9600 Video Processing Chassis



The Model VHD962 Composite Video Decoder Module is part of Delta's 9600 Series Video Processing Chassis. The module is a network appliance designed to decompress NTSC or PAL video for transmission over IP networks. The VHD962 provides a practical, cost-effective means to add digital, Standard Definition (SD) sensors to new or existing IP networks. The module can be combined with other 9600 series modules in the video processing chassis to support video-over-IP applications with diverse video sources. Delta's Video Processing Chassis supports encoding and decoding of HD/SD-SDI, Composite, and DVI/HDMI video formats for ground stations, operations centers, or classrooms.

Utilizing industry-standard H.264 compression, along with flexible adjustments for video resolutions, compression parameters, and network settings, the VHD962 can be configured to deliver high-quality video from any network. The VHD962 provides standard analog composite video and audio outputs. The module is easily configured via the Ethernet port.

A division of Delta Information Systems, Inc.

300 Welsh Road, Building 3 • Horsham, PA 19044-2294 • Tel (215) 657-5270 • Fax (215) 657-5273 • www.deltadigitalvideo.com

Questi prodotti sono distribuiti e supportati in Italia da:

**Instrumentation
Devices** 

Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)

ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - www.instrumentation.it

VIDEO INPUT

Ports One
Format NTSC/PAL
Connector BNC

VIDEO COMPRESSION

Algorithm H.264
Format HP/MP/BP
Resolutions 480i/576i
Scaling HH/HV/HH-HV
Frame Rate 25/29.97/30
GOP Structure Inter/Intra; Infinite/Variable Size

TRANSPORT STREAM

Ports One
Protocol MPEG-2 Transport Stream
RTP
Data Rate 64Kbps to 10Mbps
Format 10/100 Ethernet IP
Configuration DHCP or Static Address
Selectable Ports
Auto Sense Full/Half Duplex
Unicast/Multicast

CONTROL

Ports One
Format TCP/IP
Protocol Delta's 3-character mnemonics/HTML

AUDIO INPUT

Ports One
Channels None, Left, Right, Stereo
Format Balanced (Line Level)
Levels 2.8Vp-p (1Vrms)
Impedance 10K Ohms
Connector 3.5mm

AUDIO DECOMPRESSION

Algorithm One
Format MPEG-1 Layer II
Sample Rates 8K/16Ksps
Sync Lip synchronized with video

ENVIRONMENTAL

Temp (Op) -20°C to +60°C
Temp (Storage) -55°C to +85°C
Humidity 5%-95% RH, non-condensing

POWER

Volts +12VDC
Watts 7W

SIZE

Chassis Compatible with 9600 VPC (16-Slot) & 9680 VPC (8-Slot)



©2016 Delta Information Systems, Inc.
All rights reserved. Revision 0108

A division of Delta Information Systems, Inc.

300 Welsh Road, Building 3 • Horsham, PA 19044-2294 • Tel (215) 657-5270 • Fax (215) 657-5273 • www.deltadigitalvideo.com

Questi prodotti sono distribuiti e supportati in Italia da:



Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)

ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - www.instrumentation.it