

### FEATURES

- Real-time digital transmission of HD/SD full motion imagery
- H.264/MPEG-4 AVC (Part 10) Baseline/Main/High Profiles (Optional MPEG-2)
- HD/SD-SDI or Composite Video Input Interface
- 1080p/1080i/720p/480i/576i
- Primary/Secondary Video Encoding
- MPEG-2 compliant TS multiplexing
- Synchronous Serial or Ethernet TS Interfaces
- Fully configurable network interface
- Data Rates from 128Kbps to 25Mbps
- <50ms Encode Latency
- Stereo/dual-channel audio inputs per channel
- MPEG-1 Layer I/II Audio Compression
- Metadata Support
  - ◆ Synchronous VANC
  - ◆ Serial
  - ◆ Ethernet
  - ◆ Optional KLV Encoding
- MISB/STANAG Compliant
- IRIG-B Time Input (Optional)
- Serial or Ethernet port configurable
- Airborne Qualified Package



The Model 6810R HD/SD Video compresses video and audio signals, multiplexing them with metadata and other system information for real-time video transmission applications. The 6810R is capable of encoding HD/SD-SDI or composite analog video with resolutions up to 1080p. Utilizing the H.264 (MPEG-4 AVC Part 10) video compression algorithm, the encoder provides high quality video transmission at various resolutions and a wide range of bandwidths. The unit is built on an advanced multimedia architecture that provides encoding at all H.264 profiles up to Level 4.2. A "Primary/Secondary" encoding feature enables a second, lower resolution, lower bit rate copy of the video input to be independently configured and streamed simultaneously.

Designed for any airborne application, and specifically military ISR missions, the 6810R is compliant with the full motion video standards developed by the US Government's Motion Imagery Standards Board (MISB). This includes compliance with the video compression, KLV metadata, and transport stream profiles required to ensure interoperability in US and Allied processing, dissemination, and exploitation (PED) systems. Full DO-160/MIL-810 environmental and EMI qualification ensures the 6810R meets flight-worthiness requirements.

The 6810R is easily integrated into any FMV system, supporting legacy composite and SMPTE SD/HD/3G-SDI standards. The unit provides Ethernet and synchronous serial transport interfaces along with multi-format metadata interfaces. Serial or Telnet control, and an easy-to-use web GUI are provided for encoder set-up.

A division of Delta Information Systems, Inc.

747 Dresher Road, Suite 125 • Horsham, PA 19044-2247 • Tel (215) 657-5270 • Fax (215) 657-5273 • [www.deltadigitalvideo.com](http://www.deltadigitalvideo.com)

### VIDEO INPUT

**Ports** One  
**Format** SD/HD/3G-SDI (SMPTE) or Composite  
**Levels** .3Vp-p; 75 Ohms/1Vp-p, 75 Ohms  
**Connector** Circ-Mil, BNC, or TNC

### VIDEO COMPRESSION

**Algorithm** H.264 /MPEG-4 AVC (Part 10)  
**Format** Baseline/Main/High  
**Resolutions** 1080p/1080i/720p/480i/576i  
**Frame Rate** 1-60  
**GOP Structure** Inter/Intra; Variable Size

### TRANSPORT STREAM

**Ports** Two  
**Protocol** ISO/IEC 13818-1  
MPEG-2 Transport Stream  
Video/Audio/Data

**Format** 10/100/1000 Ethernet IP  
**Configuration** DHCP or Static Address  
Selectable Ports  
Auto Sense Full/Half Duplex  
Unicast/Multicast

**Data Rate** 128Kbps - 25Mbps  
**Connector** RJ-45  
**Format** RS-422  
**Configuration** Synchronous Serial  
**Data Rate** 128Kbps - 20Mbps  
**Connector** Circular MIL

### METADATA INTERFACE

**Ports** Three  
**Protocol** KLV/Clear  
**Format** SDI-VANC/Ethernet/Serial  
**Connector** Circular MIL

### TIME INTERFACE

**Ports** One  
**Protocol** 1PPS Sync/Free-run/IRIG-B  
**Format** 0-10Vp-p; 50 Ohms  
**Connector** Circular MIL

### CONTROL

**Ports** Two  
**Format** RS-232/RS-422; Telnet/Web Browser  
**Protocol** Delta's 3-character mnemonics

### AUDIO INPUT

**Ports** Two (one stereo)  
**Channels** None, Left, Right, Stereo  
**Format** Balanced (Line Level)  
**Levels** 2.8Vp-p (1Vrms)  
**Impedance** 10K Ohms  
**Connector** Circular MIL

### AUDIO COMPRESSION

**Algorithm** One  
**Format** MPEG-1 Layer I/II  
**Sample Rates** 48Ksps  
**Sync** Lip synchronized with video

### LATENCY

**Encoder** <50ms (per channel)  
**Enc/Dec Tandem** <100ms

### ENVIRONMENTAL (DO-160D)

**Temp/Alt (Op)** DO-160D, Section 4, Category D2  
-55°C to +70°C (+85°C Capable)

**Temp/Alt (Non-Op)** DO-160D, Section 4, Category D2  
-55°C to +85°C

**Humidity** DO-160D, Section 6, Category B  
5%-95% RH, non-condensing

**Vibration** DO-160D, Section 8, Category S,  
Figure 8-3, Profile M

**Shock** DO-160D, Section 7, Category A,  
Figure 7-2, Operational  
(6g, 11ms, sawtooth)

### EMI

**MIL-STD-461E** CS101, CS114-116, RS103,  
RE102, CE-102

**DO-160E** Section 18, AF Conducted  
Susceptibility  
Section 21, Conducted Emissions

### POWER

**Volts** +28VDC  
**Watts** 11W  
**Connector** Circular MIL

### SIZE / WEIGHT

**Chassis** 5.6"D x 3.5"W x 2.475"H / 1.7lbs.

©2014 Delta Information Systems, Inc.  
All rights reserved. Revision 0417

A division of Delta Information Systems, Inc.

747 Dresher Road, Suite 125 • Horsham, PA 19044-2247 • Tel (215) 657-5270 • Fax (215) 657-5273 • [www.deltadigitalvideo.com](http://www.deltadigitalvideo.com)



Instrumentation Devices Srl

Via Acquanera 29 - 22100 COMO (Italy)

ph +39 031 525 391- fax +39 031 507 984

info@instrumentation.it - [www.instrumentation.it](http://www.instrumentation.it)